

# VP-2 Dual Extended Range VU/PPM Meter

---



The VP-2 is a two channel extended range audio meter.

The pushbuttons on the front panel select either VU or PPM ballistics for each channel. The logical multi-colour LED display covers the range from -40 to +21 VU or PPM levels with extreme accuracy. Quality LEDs ensure optimum visibility, and eliminate cross-illumination from adjacent LEDs.

Audio inputs are the balanced XLR type. The unit will also accept unbalanced inputs.

---

## VP-2 Specifications

### **Power Requirements**

115 VAC, 60 Hz or 230 VAC, 50 Hz; 11 W

## Analog Audio Inputs

### **Number of Inputs**

1 per channel, 2 channels total

### **Input Impedance**

40 kohms balanced

### **Input Signal Level**

+27 dBm maximum

### **Input Connectors**

XLR, female (x2)

### **Common Mode Rejection**

-85 dB @ 60 Hz

## Display

### **Range**

-40 to + 21 VU or PPM (front panel selectable)

### **Accuracy**

+/- 0.5 dB, 20 Hz to 20 kHz

### **Display Type**

LED, multi-colour

## Physical Dimensions (Inches)

### **VP-2**

8.1 W x 1.9 H x 5.1 D

[Download VP-2 PDF File](#)

---



---

[Home](#) | [Contacting Us](#) | [Dealers](#) | [Products](#) | [New Products](#) | [Calendar](#) | [Product Reviews](#) |  
| [Software](#) | [Tech. Tips](#) | [Installations](#)

---

If you have questions or comments, you can contact us toll free from Canada and US at 1-888-293-1071 or e-mail us at [vrl@videoquip.com](mailto:vrl@videoquip.com). We appreciate your business.

Copyright © 1996-2002 Videoquip Research Limited