

VP-2 Dual Extended Range VU/PPM Meter



The VP-2 is a two channel extended range audio meter.

The pushbuttons on the front panel select either VU or PPM ballistics for each channel. The logical multi-colour LED display covers the range from -40 to +21 VU or PPM levels with extreme accuracy. Quality LEDs ensure optimum visibility, and eliminate cross-illumination from adjacent LEDs.

Audio inputs are the balanced XLR type. The unit will also accept unbalanced inputs.

VP-2 Specifications

Power Requirements

115 VAC, 60 Hz or 230 VAC, 50 Hz; 11 W

Analog Audio Inputs

Number of Inputs

1 per channel, 2 channels total

Input Impedance

40 kohms balanced

Input Signal Level

+27 dBm maximum

Input Connectors

XLR, female (x2)

Common Mode Rejection

-85 dB @ 60 Hz

Display

Range

-40 to + 21 VU or PPM (front panel selectable)

Accuracy

+/- 0.5 dB, 20 Hz to 20 kHz

Display Type

LED, multi-colour

Physical Dimensions (Inches)

VP-2

8.1 W x 1.9 H x 5.1 D

[Download VP-2 PDF File](#)



[Home](#) | [Contacting Us](#) | [Dealers](#) | [Products](#) | [New Products](#) | [Calendar](#) | [Product Reviews](#) |
| [Software](#) | [Tech. Tips](#) | [Installations](#)

If you have questions or comments, you can contact us toll free from Canada and US at 1-888-293-1071 or e-mail us at vrl@videoquip.com. We appreciate your business.

Copyright © 1996-2002 Videoquip Research Limited